



TPG 366 Controller for 6 Gauges




Similar Image

TPG 366 Controller for 6 Gauges

- For operation of six gauges with analog output signal
- Brilliant display
- Simultaneous display of six pressure readings
- Six freely configurable relay set points
- Versatile connectivity: USB, RS-485, Ethernet
- Direct data storage on USB flash memory (data and settings)
- Can be used as table top or as rack mount unit

Dimensions



Technical Data	TPG 366 Controller for 6 Gauges
Ambient temperature	5-50 °C 41-122 °F 278-323 K
Automatic changeover: Pirani-cold cathode	Configurable
Connection for gauge	6
Display rate	10 Hz
Error signal: Working contact, potential-free	1 Pcs.
Filter time constant, rapid/normal/slow	0.02 s/0.15 s/0.75 s
I/O interfaces	USB, RS-485, Ethernet
Mains requirement: frequency (range)	50/60 Hz
Mains requirement: power consumption	≤ 200 VA
Mains requirement: voltage (range)	100–240 V
Measurement range	$5 \cdot 10^{-11} - 5.5 \cdot 10^4$ hPa
Measurement rate	100 Hz
Measuring channel	6 Pcs.
Power consumption max.	200 VA
Protection category	IP30
Safety	CE, UL
Set point: Changeover contact, potential-free	6 Pcs.

Technical Data	TPG 366 Controller for 6 Gauges
Set point: Current AC	1 A
Set point: Current DC	0.5 A
Set point: Voltage AC	30 V AC
Set point: Voltage DC	60 V DC
Set point number	6 Pcs.
Signal output: Measuring value, analog	0 – 10 V
Temperature: Storage	-20-60 °C -4-140 °F 253-333 K
Weight	2.2 kg 4.85 lb

Order number	
TPG 366	PT G28 770

Accessories	
Cables Measurement cables	
Measurement Cable, 1 m	PT 448 248 -T
Measurement cable, 3 m	PT 448 250 -T
Measurement cable, 6 m	PT 448 251 -T
Measurement cable, 10 m	PT 448 252 -T
Measurement Cable, 15 m	PT 448 253 -T
Measurement Cable, 20 m	PT 448 254 -T
Measurement Cable, 25 m	PT 448 255 -T
Measurement Cable, 30 m	PT 448 256 -T
Measurement Cable, 35 m	PT 448 257 -T
Measurement Cable, 40 m	PT 448 258 -T
Measurement Cable, 45 m	PT 448 259 -T
Measurement Cable, 50 m	PT 448 260 -T
Software Display & Data logging	
Software for display and data logging for ActiveLine	PT 882 550 -T

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a
perfect vacuum solution?
Please contact us:

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com

All data subject to change without prior notice.

PFEIFFER  **VACUUM**